WHAT IS CLAIMED IS:

 A method of electrochemically and mechanically planarizing a surface of a substrate, comprising:

- (a) providing a basin containing an electrically conductive solution and an electrode disposed therein;
 - (b) disposing a polishing medium in the electrically conductive solution;
- (c) positioning a substrate against the polishing medium so that a surface of the substrate contacts the electrically conductive solution;
- (d) applying a first potential between the polishing medium and the electrode for a first time period; and
- (e) applying a second potential between the polishing medium and the electrode for a second time period.
- 2. The method of claim 1, wherein the second potential is a zero potential.
- The method of claim 1, wherein the second potential is lower than the first potential.
- 4. The method of claim 1, wherein the first potential is a pulsed potential with a waveform.
- 5. The method of claim 1, wherein the first potential is a pulsed potential with a waveform and the second potential is a pulsed potential with a waveform.
- The method of claim 1, wherein the first potential is a pulsed potential with a waveform and the second potential is a pulsed potential with a waveform and a negative polarity.
- 7. The method of claim 1, wherein the first potential is a pulsed potential with a waveform and the second potential is a zero potential.

PATENT

Attorney Docket No.: AMAT/6877/ALRT/CMP/CMP/RKK

Express Mail No.: EV324942761US

8. The method of claim 1, wherein the first potential is modulated within a predefined range of potentials.

- 9. The method of claim 1, wherein the second potential is modulated within a predefined range of potentials.
- 10. The method of claim 1, further comprising repeating steps (d) and (e) for a third time period.
- 11. The method of claim 1, wherein applying the first potential comprises: applying a third potential between the polishing medium and the electrode for a third time period: and

applying a fourth potential between the polishing medium and the electrode for a fourth time period.

- 12. The method of claim 11, wherein the third potential is a pulsed potential with a waveform and the fourth potential is a pulsed potential with a waveform.
- 13. The method of claim 1, wherein applying the second potential comprises: applying a third potential between the polishing medium and the electrode for a third time period: and

applying a fourth potential between the polishing medium and the electrode for a fourth time period.

- 14. The method of claim 13, wherein the third potential is a pulsed potential with a waveform and the fourth potential is a pulsed potential with a waveform.
- 15. The method of claim 1, wherein the first time period is greater than the second time period.

PATENT

Attorney Docket No.: AMAT/6877/ALRT/CMP/CMP/RKK

Express Mail No.: EV324942761US

16. The method of claim 1, further comprising applying a third potential between the polishing medium and the electrode for a third time period.

- The method of claim 16, wherein the third potential is a pulsed potential with a waveform.
- 18. The method of claim 16, wherein the first potential is a pulsed potential with a waveform, the second potential is a pulsed potential with a waveform, and the third potential is a pulsed potential with a waveform.
- 19. The method of claim 1 further comprising
- (f) applying a third potential between the polishing medium and the electrode for a third time period; and

repeating steps (d) through (f) for a period of time.